

SAFETY DATA SHEET

In accordance with (EU) Nr. 1907/2006

Revision Date: 1.02.2021 replace vers. from 17.01.2019

Tradename: CULR™ Art Pigment for Epoxy – Polished Silver

page 1/14

SECTION 1: IDENTIFICATION OF SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1. Product identifier

Tradename: CULR™ Art Pigment for Epoxy – Polished Silver

1.2. Relevant identified uses of the substances or mixture and uses advised against

Relevante identified uses of the substance or mixture

Industry sector: Industrial Performance Chemicals
Paints, lacquers and varnishes industry
Polymers industry
Printing Inks Industry

Type of use: Colourant preparation

1.3. Details of the supplier of the safety data sheet

Easy Composites Ltd
Unit 39 Park Hall Business Village
Stoke on Trent, ST3 5XA. United Kingdom.
Phone: +44 (0)1782 454499

Information to substance / mixture:

Division: Technical

E-mail: technical@glasscastresin.com

1.4. Emergency telephone number

Emergency CONTACT (Office Hours) Phone: +44 (0)1782 454499

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance / mixture

Classification (Regulation (EC) No.1272/2008):

Not a dangerous substance according to GHS.

2.2. Label elements

Labeling (Regulation (EC) No.1272/2008):

Not a dangerous substance or mixture according to the Globally Harmonised System (GHS).

Additional Labelling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

3.1. Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. INDEX No. Registration No.	Classification Regulation (EC) No. 1272/2008)	Concentration (% w/w)

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830

Revision Date: 01.02.2021 replace vers. 17.01.2019

Tradename: CULR™ Art Pigment for Epoxy – Polished Silver

page 2/14

Aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	≥ 25 - < 50
Phosphoric acid, C11-14-isoalkyl esters, C13-rich	154518-38-4 (52933-07-0) 01-2119976356-25	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 2; H411	≥ 3 - < 10
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	≥ 0.0025 - < 0.025
reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	≥ 0.0002 - < 0.0015

For explanation of abbreviations see section 16.

SECTION 4: FIRST AID MEASURES

4.1. Discription of first aid measures

General advice:

No hazards which requires special first aid measures.

Move the victim to fresh air.

Do not leave the victim unattended.

If inhaled:

If unconscious place in recovery position and seek medical advice.

If symptoms persist, call a physician.

In case of skin contact:

Wash off immediately with soap and plenty of water.

In case of eye contact:

Immediately flush eye(s) with plenty of water.

Remove contact lenses.

If swallowed:

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2. Most important symptoms and effects, both acute and delayed

None known.

4.3. Indication of any immediate medical attention and special treatment needed

This information is not available..

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media:

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830

Revision Date: 01.02.2021 replace vers. 17.01.2019

Tradename: CULR™ Art Pigment for Epoxy – Polished Silver

page 3/14

Suitable extinction agents:

Dry sand
ABC powder
Foam

Unsuitable extinguishing media:

Water

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Special protective equipment for firefighting:

Wear self contained breathing apparatus for firefighting if necessary.

Further information:

Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Evacuate personnel to safe areas.

6.2. Environment precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Wipe up with absorbent material (e.g. cloth, fleece).

Do not flush with water.

Keep in suitable, closed containers for disposal.

6.4. Cross Reference to other sections

For personal protection see section 8.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling:

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the application area.

Advice on protection against fire and explosion:

Normal measures for preventive fire protection.

Hygiene measures:

General industrial hygiene practice.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers:

Earthing of containers and apparatuses is essential.

Take measures to prevent the build up of electrostatic charge.

Use explosion-proof equipment. Store in original container.

Electrical installations / working materials must comply with the technological safety standards.

Advice on common storage:

Do not store near acids.

Do not store together with oxidizing and self-igniting products.

Keep away from oxidizing agents and strongly acid or alkaline materials.

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830

Revision Date: 01.02.2021 replace vers. 17.01.2019

Tradename: CULR™ Art Pigment for Epoxy – Polished Silver

page 4/14

Keep away from oxidizing agents and strongly acid or alkaline materials.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials
in order to avoid exothermic reactions..

Further information on storage conditions:

No decomposition if stored and applied as directed.

7.3. Specific end use(s)

This information is not available.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Aluminium powder (stabilized)	7429-90-5	TWA (Inhalable)	10 mg/m ³	GB EH40
Further information		The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used..		
		TWA (Respirable fraction)	4 mg/m ³	GB EH40
Further information		The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
		TWA (inhalable dust)	10 mg/m ³	GB EH40
Further information		For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be		

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830

Revision Date: 01.02.2021 replace vers. 17.01.2019

Tradename: **CULR™ Art Pigment for Epoxy – Polished Silver**

page 5/14

	<p>subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>		
	TWA (Respirable dust)	4 mg/m ³	GB EH40
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>		

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830

Revision Date: 01.02.2021 replace vers. 17.01.2019

Tradename: CULR™ Art Pigment for Epoxy – Polished Silver

page 6/14

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	long term local effects	3.72 mg/m ³
	Consumers	Oral	long term systemic effects	3.95 mg/kg
	Workers	Inhalation	long term systemic effects	3.72 mg/m ³
Phosphoric acid, C11- 14-isoalkyl esters, C13-rich	Workers	Inhalation	long term systemic effects	34.94 mg/m ³
	Workers	Skin contact	long term systemic effects	100.13 mg/kg
	Consumers	Inhalation	long term systemic effects	10.43 mg/m ³
	Consumers	Skin contact	long term systemic effects	60.08 mg/kg
	Consumers	Ingestion	long term systemic effects	6.01 mg/kg
2,2',2"-nitrilotriethanol	Workers	Inhalation	long term local effects	5 mg/m ³
	Workers	Skin contact	long term systemic effects	6.3 mg/kg
	Workers	Inhalation	long term systemic effects	5 mg/m ³
	Consumers	Inhalation	long term local effects	1.25 mg/m ³
	Consumers	Ingestion	long term systemic effects	13 mg/kg
	Consumers	Skin contact	long term systemic effects	3.1 mg/kg
	Consumers	Inhalation	long term systemic effects	1.25 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
Phosphoric acid, C11-14-isoalkyl esters, C13-rich	Fresh water	6.31 µg/l
	Fresh water sediment	0.113 mg/kg
	Sporadic Release	63.1 µg/l
	Marine water	0.631 µg/l
	Marine sediment	0.0113 mg/kg
	STP	10 mg/l

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830

Revision Date: 01.02.2021 replace vers. 17.01.2019

Tradename: **CULR™ Art Pigment for Epoxy – Polished Silver**

page 7/14

	Soil	0.0188 mg/kg
2,2',2"-nitrioltri-ethanol	Soil	0.151 mg/kg
	Fresh water	0.32 mg/l
	Fresh water sediment	1.7 mg/kg
	clarification plant	10 mg/l
	Marine water	0.032 mg/l
	Marine sediment	0.17 mg/kg
1,2-benziso-thiazol-3(2H)-one	Fresh water	0.00403 mg/l
	Marine water	0.000403 mg/l
	STP	0.00103 mg/l

8.2. Exposure controls

Personal protective equipment

Eye protection:

Goggles

Safety glasses

Hand protection:

Material: Solvent resistant gloves (butyl-rubber)

Remarks: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Respiratory protection:

Use suitable breathing protection if workplace concentration requires.

No personal respiratory protective equipment normally required.

8.3. Environment exposure controls

Water:

The product should not be allowed to enter drains, water courses or soil.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Appearance

Appearance:	liquid
Colour:	silver
Odour:	characteristic
Odour Threshold:	no data available
pH:	6-8
	Concentration: 100%
Freezing point:	no data available
Boiling point/boiling range:	> 100 °C
Flash point:	> 100 °C
Evaporation rate:	no data available

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830

Revision Date: 01.02.2021 replace vers. 17.01.2019

Tradename: CULR™ Art Pigment for Epoxy – Polished Silver

page 8/14

Flammibility(solid, gas)	no data available
Self-ignition:	no data available
Auto-ignition temperature:	no data available
Smoldering temperature:	no data available
Decomposition temperature:	no data available
Explosive properties:	no data available
Oxidizing properties:	no data available
Upper explosion limit / Upper flammability limit:	no data available
Lower explosion limit / Lower flammability limit:	no data available
Vapour pressure:	no data available
Relative vapour density:	no data available
Relative density:	no data available
Density:	no data available
Bulk density:	no data available
Water solubility:	no data available
Solubility in other solvents:	no data available
Partition coefficient: noctanol/water:	no data available
Decomposition temperature:	no data available
Viscosity, dynamic:	no data available
Viscosity, kinematic:	no data available
Flow time:	no data available

9.2. Other information

No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical Stability

No decomposition if stored and applied as directed.

10.3. Possibility of hazardous reactions

Hazardous reactions:

Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

10.4. Conditions to avoid

Do not allow evaporation to dryness.

No data available.

10.5. Incompatible Materials

Materials to avoid:

Acids

Bases

Oxidizing agents

10.6. Hazardous decomposition products

Contact with water or humid air:

This information is not available.

Thermal decomposition:

This information is not available.

SECTION 11: TOXICOLOGIC INFORMATION

11.1. Acute Toxicity

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830

Revision Date: 01.02.2021 replace vers. 17.01.2019

Tradename: CULR™ Art Pigment for Epoxy – Polished Silver

page 9/14

Not classified based on available information.

Product:

Acute inhalation toxicit: Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

aluminium powder (stabilised):

Acute inhalation toxicit: LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity: Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicit: LC50 (Rat): 0.4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The component/mixture is highly toxic after short term inhalation.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute oral toxicity: Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicit: Assessment: The component/mixture is highly toxic after short term inhalation.

Acute dermal toxicity Assessment: The component/mixture is highly toxic after single contact with skin.

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: No skin irritation

Components:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich:

Result: Skin irritation

1,2-benzisothiazol-3(2H)-one:

Result: Skin irritation

Serious eye damage/eye irritation:

Not classified based on available information.

Product:

Result: No skin irritation

Components:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich:

Result: Corrosive

1,2-benzisothiazol-3(2H)-one:

Result: Corrosive

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Result: Corrosive

Respiratory or skin sensitisation

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830

Revision Date: 01.02.2021 replace vers. 17.01.2019

Tradename: CULR™ Art Pigment for Epoxy – Polished Silver

page 10/14

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Result: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT – single exposure

Not classified based on available information.

STOT – repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further Information

Product:

Result: No data available

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity:

Product:

Ecotoxicology Assessment:

Short-term (acute) aquatic hazard: This product has no known ecotoxicological effects.

Long-term (chronic) aquatic hazard: This product has no known ecotoxicological effects.

Components:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich:

Toxicity to fish: LC50 (Oncorhynchus mykiss (rainbow trout)): 24 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): 6.31 mg/l
Exposure time: 48 h

Toxicity to algae: EC50 (algae): 150 mg/l
Exposure time: 72 h

1,2-benzisothiazol-3(2H)-one:

M-Factor (Short-term (acute) aquatic hazard): 1

Ecotoxicology Assessment:

Short-term (acute) aquatic hazard: Very toxic to aquatic life.

Long-term (chronic) aquatic hazard: Toxic to aquatic life with long lasting effects.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830

Revision Date: 01.02.2021 replace vers. 17.01.2019

Tradename: CULR™ Art Pigment for Epoxy – Polished Silver

page 11/14

M-Factor (Short-term (acute): 100
aquatic hazard)

M-Factor (Long-term (chronic): 100
aquatic hazard)

Ecotoxicology Assessment:

Short-term (acute) aquatic hazard: Very toxic to aquatic life.

Long-term (chronic) aquatic hazard: Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

Product:

Assessment: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6. Other adverse effects

Product:

Additional ecological information No data available

SECTION 13: DISPOSAL CONSIDERATIONS

European Waste Catalogue: 08 01 11 - waste paint and varnish containing organic solvents or other dangerous substances.

13.1. Waste treatment methods

Product:

In accordance with local and national regulations.

Contaminated packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal.

In accordance with local and national regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number

ADR: Not regulated as a dangerous good

IMDG: Not regulated as a dangerous good

IATA: Not permitted for transport

14.2 UN proper shipping name

ADR: Not regulated as a dangerous good

IMDG: Not regulated as a dangerous good

IATA: Not permitted for transport

14.3 Transport hazard class(es)

ADR: Not regulated as a dangerous good

IMDG: Not regulated as a dangerous good

IATA: Not permitted for transport

14.4 Packing group

ADR: Not regulated as a dangerous good

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830

Revision Date: 01.02.2021 replace vers. 17.01.2019

Tradename: CULR™ Art Pigment for Epoxy – Polished Silver

page 12/14

IMDG: Not regulated as a dangerous good

IATA (Cargo): Not permitted for transport

IATA (Passenger): Not permitted for transport

14.5 Environmental hazards

ADR: Not regulated as a dangerous good

IMDG: Not regulated as a dangerous good

14.6. Special precautions for user

Remarks: Due to the risk of hydrogen development we recommend to refrain from airfreighting this/these product(s).

Not classified as dangerous in the meaning of transport regulations.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of

Very High Concern for Authorisation (Article 59):

Not applicable

Regulation (EC) No 1005/2009 on substances that :
deplete the ozone layer:

Not applicable

Regulation (EU) 2019/1021 on persistent organic :
pollutants (recast):

Not applicable

REACH - Restrictions on the manufacture, placing on :
the market and use of certain dangerous substances,
preparations and articles (Annex XVII)

Conditions of restriction for the
following entries should be
considered:

aluminium powder (stabilised)
(Number on list 40) Phosphoric acid,
C11-14-isoalkyl esters, C13-rich
(Number on list 3) 2-
dimethylaminoethanol (Number on list
40, 3) 2,2'-iminodiethanol (Number on
list 3) reaction mass of 5-chloro-2-
methyl-2H-isothiazol-3-one and 2-
methyl-2H-isothiazol-3-one (3:1)
(Number on list 3) pyridine-2-thiol 1-
oxide, sodium salt (Number on list 3)

15.2. Chemical safety assessment

SECTION 16: OTHER INFORMATION

Full text of H-Statements:

H228	Flammable solid
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830

Revision Date: 01.02.2021 replace vers. 17.01.2019

Tradename: CULR™ Art Pigment for Epoxy – Polished Silver

page 13/14

Acute Tox. :	Acute toxicity
Aquatic Acute :	Short-term (acute) aquatic hazard
Aquatic Chronic :	Long-term (chronic) aquatic hazard
Eye Dam. :	Serious eye damage
Flam. Sol. :	Flammable solids
Skin Corr. :	Skin corrosion
Skin Irrit. :	Skin irritation
Skin Sens. :	Skin sensitisation
GB EH40:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA:	Long-term exposure limit (8-hour TWA reference period)

Legend

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AICS	Australian Inventory of Chemical Substances
ASTM	American Society for the Testing of Materials
bw	Body weight
CLP	Classification Labelling Packaging Regulation Regulation (EC) No 1272/2008
CMR	Carcinogen, Mutagen or Reproductive Toxicant
DIN	Standard of the German Institute for Standardisation
DMEL	Derived Minimal Effect Level (genotoxic substances)
DNEL	Derived No Effect Level
DSL	Domestic Substances List (Canada)
ECHA	European Chemicals Agency
EC-Number	European Community number
ECx	Concentration associated with x% response
ELx	Loading rate associated with x% response
EmS	Emergency Schedule
ENCS	Existing and New Chemical Substances (Japan)
ErCx	Concentration associated with x% growth rate response
GHS	Globally Harmonized System
GLP	Good Laboratory Practice
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50	Half maximal inhibitory concentration
ICAO	International Civil Aviation Organization
IECSC	Inventory of Existing Chemical Substances in China
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
ISHL	Industrial Safety and Health Law (Japan)
ISO	International Organisation for Standardization
KECI	Korea Existing Chemicals Inventory
LC50	Lethal Concentration to 50 % of a test population
LD50	Lethal Dose to 50% of a test population (Median Lethal Dose)
MARPOL	International Convention for the Prevention of Pollution from Ships
n.o.s.	Not Otherwise Specified
NO(A)EC	No Observed (Adverse) Effect Concentration
NO(A)EL	No Observed (Adverse) Effect Level
NOELR	No Observable Effect Loading Rate
NZIoC	New Zealand Inventory of Chemicals
OECD	Organization for Economic Co-operation and Development
OPPTS	Office of Chemical Safety and Pollution Prevention
PBT	Persistent, Bioaccumulative and Toxic substance
PICCS	Philippines Inventory of Chemicals and Chemical Substances
(Q)SAR	(Quantitative) Structure Activity Relationship

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830

Revision Date: 01.02.2021 replace vers. 17.01.2019

Tradename: CULR™ Art Pigment for Epoxy – Polished Silver

page 14/14

REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SADT	Self-Accelerating Decomposition Temperature
SDS	Safety Data Sheet
TCSI	Taiwan Chemical Substance Inventory
TRGS	Technical Rule for Hazardous Substances
TSCA	Toxic Substances Control Act (United States)
UN	United Nations
vPvB	Very Persistent and Very Bioaccumulative

Decimal notation: "thousands" places are identified with a dot (for example, "2.000 mg/kg" means "two thousand mg/kg"). Decimal places are identified with a comma (for example, "1,35 g/cm³" means "one point three five g/cm³").

This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. GlassCast makes no warranties, express or implied, as to the information accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of GlassCast products for its particular application. Nothing included in this information waives any of GlassCast's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing.

Any existing intellectual/industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. Material Safety Data Sheets providing safety precautions, that should be observed when handling or storing GlassCast products, are available upon request and are provided in compliance with applicable law. You should obtain and review the applicable Material Safety Data Sheet information before handling any of these products.

For additional information, please contact GlassCast.