

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : GlassCast 10/50 Epoxy Resin  
UFI 3RT1-H94T-V007-8VEM

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Type of Application (Use) : Electrical Insulation

Recommended restrictions : Reserved for industrial and professional use.  
on use

#### 1.3 Details of the supplier of the safety data sheet

**Company name:** Easy Composites Ltd  
Unit 39, Park Hall Business Village  
Longton, Stoke on Trent  
Staffordshire  
ST3 5XA  
United Kingdom

**Tel:** +44 (0) 1782 454499

**Email:** sales@easycomposites.com

#### 1.4 Emergency telephone number

+44 (0) 1782 454499  
(office hours only)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 1B	H360F: May damage fertility.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H360F May damage fertility.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

### Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P391 Collect spillage.

### Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxypropoxy)phenyl]propane

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

1,4-bis(2,3 epoxypropoxy)butane

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl Sebacate

### Additional Labelling

EUH205 Contains epoxy constituents. May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : Modified epoxy resin

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411  specific concentration limit Eye Irrit. 2; H319 ≥ 5 % Skin Irrit. 2; H315 ≥ 5 % Eye Irrit. 2; H319 ≥ 5 % Skin Irrit. 2; H315 ≥ 5 %	≥ 50 - ≤ 100
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2 271-846-8 603-103-00-4 01-2119485289-22	Skin Irrit. 2; H315 Skin Sens. 1; H317 Repr. 1B; H360F	≥ 10 - < 12,5
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8 219-371-7 603-072-00-7 01-2119494060-45	Acute Tox. 4; H302 Acute Tox. 4; H312 Acute Tox. 4; H332 Eye Dam. 1; H318 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 3; H412	≥ 5 - < 7
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl Sebacate	1065336-91-5 01-2119491304-40	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1  M-Factor (Chronic aquatic toxicity): 1	≥ 0,1 - < 0,25

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Keep warm and in a quiet place.  
Show this safety data sheet to the doctor in attendance.  
Take off all contaminated clothing immediately.
- If inhaled : Move to fresh air.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
Do NOT use solvents or thinners.  
If on clothes, remove clothes.  
If skin irritation persists, call a physician.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
If eye irritation persists, consult a specialist.  
If easy to do, remove contact lens, if worn.
- If swallowed : Keep at rest.  
Do not induce vomiting without medical advice.  
Keep respiratory tract clear.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : irritant effects  
Redness  
sensitising effects

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Foam  
Sand  
Carbon dioxide (CO<sub>2</sub>)  
Water mist

; `Ugg7 Ugh%\$# \$'9 dcl m7 Ugh]b[ 'F Yg]b

Version  
10.0 SDB\_GBRevision Date:  
25.06.2024Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

Unsuitable extinguishing media : Water spray jet

) "&amp;GdYVJ\ UhUXg'Uf]g]b[ 'Zca 'h Ygi VgUbwW' cf'a ]l h fY'

Specific hazards during fire-fighting : The pressure in sealed containers can increase under the influence of heat.  
Cool closed containers exposed to fire with water spray.

) " '5 Xj jWV Zf'ZfYQ[ \ hfg'

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.Further information : In the event of fire and/or explosion do not breathe fumes.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Immediately evacuate personnel to safe areas.  
Prevent fire extinguishing water from contaminating surface water or the ground water system.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

G97 HCB\*.5 WXYbHJ'fYUgYa YUgi fYg'

\* "%DYfgcbU' dfYVU h]cbgZ dfchVWj] Y Yei ]da YbhUbX'Ya Yf[ YbWm dfcWXi fYg'

Personal precautions : Refer to protective measures listed in sections 7 and 8.  
Evacuate personnel to safe areas.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

\* "&amp;9bj jfcba YbHJ' dfYVU h]cbg'

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.  
Try to prevent the material from entering drains or water courses.  
Local authorities should be advised if significant spillages cannot be contained.

\* " 'A Yh cXg' UbX'a UhYf]U' Zf'W:bHJ]ba YbhUbX'WYUb]b[ 'i d'

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Pick up and transfer to properly labelled containers.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms. Avoid inhalation, ingestion and contact with skin and eyes. Wear personal protective equipment. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : Provide adequate ventilation. Wash hands and face before breaks and immediately after handling the product.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labelled containers.
- Advice on common storage : Keep away from oxidizing agents, strongly acid or alkaline materials and amines. Keep product and empty container away from heat and sources of ignition. Keep away from food and drink.
- Further information on storage stability : Stable at normal ambient temperature and pressure.

### 7.3 Specific end use(s)

- Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Workers	Skin contact	Acute systemic effects, Long-term systemic effects	8,33 mg/kg
	Workers	Inhalation	Acute systemic effects, Long-term local effects	12,25 mg/m <sup>3</sup>
	Consumers	Skin contact	Acute systemic ef-	3,571 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

			fects, Long-term systemic effects	
	Consumers	Ingestion	Acute systemic effects, Long-term systemic effects	0,75 mg/kg
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Workers	Skin contact	Long-term systemic effects	3,9 mg/kg
	Workers	Inhalation	Long-term systemic effects	13,8 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Fresh water	0,006 mg/l
	Marine water	0,0006 mg/l
	Intermittent releases	0,018 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0,996 mg/kg
	Marine sediment	0,0996 mg/kg
	Soil	0,196 mg/kg
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Sewage treatment plant	10 mg/l
	Fresh water	0,0072 mg/l
	Marine water	0,00072 mg/l
	Fresh water sediment	66,77 mg/kg
	Marine sediment	6,677 mg/kg
	Soil	80,12 mg/kg

## 8.2 Exposure controls

### Engineering measures

Effective exhaust ventilation system  
effective ventilation in all processing areas

### Personal protective equipment

Eye protection : Do not wear contact lenses.  
Safety glasses with side-shields conforming to EN166  
Ensure that eyewash stations and safety showers are close to the workstation location.

#### Hand protection

Material : Protective gloves complying with EN 374.

Material : butyl-rubber  
Break through time : > 480 min  
Glove thickness : 0,35 mm

Material : Neoprene  
Break through time : > 480 min  
Glove thickness : 0,35 mm

Material : Nitrile rubber  
Break through time : > 480 min  
Glove thickness : 0,35 mm

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

Remarks	:	For prolonged or repeated contact use protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	:	Protective suit
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. In the case of vapour formation use a respirator with an approved filter. Equipment should conform to EN 14387 Apply technical measures to comply with the occupational exposure limits. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.
Protective measures	:	Avoid contact with skin. Wear suitable protective equipment.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	colourless
Odour	:	slight
Odour Threshold	:	not determined
Melting point/freezing point	:	Not applicable
Boiling point/boiling range	:	> 200 °C
Upper explosion limit / Upper flammability limit	:	Not applicable
Lower explosion limit / Lower flammability limit	:	Not applicable
Flash point	:	150 °C
Auto-ignition temperature	:	Not applicable
Decomposition temperature	:	No data available
pH	:	4 - 6 Concentration: 1 %
Viscosity	:	
Viscosity, dynamic	:	700 - 1.000 mPa.s (25 °C)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

Viscosity, kinematic : not determined

### Solubility(ies)

Water solubility : not determined

Solubility in other solvents : not determined

Partition coefficient: n-octanol/water : No data available

Vapour pressure : not determined

Density : 1,12 g/cm<sup>3</sup> (25 °C)

Bulk density : not determined

Relative vapour density : not determined

### Particle characteristics

Particle size : Not applicable

## 9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Self-ignition : Not applicable

Evaporation rate : not determined

Surface tension : not determined

Sublimation point : Not applicable

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Stable under recommended storage conditions.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with the following substances:  
Bases  
Strong oxidizing agents  
Avoid amines.

### 10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

### 10.5 Incompatible materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

Materials to avoid : Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

This product may release the following:

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Acute toxicity (other routes of administration) :  
Remarks: No data available

##### Components:

##### **bis-[4-(2,3-epoxipropoxy)phenyl]propane:**

Acute oral toxicity : LD50 (Rat, female): > 2.000 mg/kg  
Method: OECD Test Guideline 420  
GLP: yes

Acute dermal toxicity : LD50 (Rat, male and female): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

#### Skin corrosion/irritation

##### Product:

Remarks : No data available

##### Components:

##### **bis-[4-(2,3-epoxipropoxy)phenyl]propane:**

Species : Rabbit  
Exposure time : 4 h  
Method : OECD Test Guideline 404  
Result : Skin irritation  
GLP : yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

### Serious eye damage/eye irritation

**Product:**

Remarks : No data available

### Respiratory or skin sensitisation

**Product:**

Remarks : No data available

### **Components:**

#### **bis-[4-(2,3-epoxipropoxy)phenyl]propane:**

Test Type : Mouse Local Lymph Node assay (LLNA)  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : May cause sensitisation by skin contact.  
GLP : yes

### Carcinogenicity

**Product:**

Remarks : No data available

### Reproductive toxicity

**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

### STOT - single exposure

**Product:**

Remarks : No data available

### STOT - repeated exposure

**Product:**

Remarks : No data available

### Repeated dose toxicity

**Product:**

Remarks : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

### Aspiration toxicity

#### Components:

**bis-[4-(2,3-epoxipropoxy)phenyl]propane:**

No aspiration toxicity classification

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : No data available

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

#### Components:

**bis-[4-(2,3-epoxipropoxy)phenyl]propane:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 1,7 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,3 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
Method: OECD Test Guideline 211  
GLP: yes

**Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl Sebacate:**

M-Factor (Acute aquatic tox- : 1

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

icity)

M-Factor (Chronic aquatic toxicity) : 1

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

#### Components:

##### **bis-[4-(2,3-epoxipropoxy)phenyl]propane:**

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available

#### Components:

##### **bis-[4-(2,3-epoxipropoxy)phenyl]propane:**

Partition coefficient: n-octanol/water : log Pow: 3,242 (25 °C)  
pH: 7,1  
Method: OECD Test Guideline 117  
GLP: yes

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : In accordance with local and national regulations.  
Container hazardous when empty.  
Do not dispose of with domestic refuse.  
Do not mix waste streams during collection.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR/RID/ADN : UN 3082  
IMDG : UN 3082  
IATA : UN 3082

### 14.2 UN proper shipping name

ADR/RID/ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(bis-[4-(2,3-epoxipropoxy)phenyl]propane)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(bis-[4-(2,3-epoxipropoxy)phenyl]propane)

IATA : Environmentally hazardous substance, liquid, n.o.s.  
(bis-[4-(2,3-epoxipropoxy)phenyl]propane)

### 14.3 Transport hazard class(es)

ADR/RID/ADN : 9  
IMDG : 9  
IATA : 9

### 14.4 Packing group

ADR/RID/ADN  
Packing group : III  
Classification Code : M6  
Hazard Identification Number : 90  
Labels : 9  
Tunnel restriction code : -  
Remarks : ADR: These substances when carried in single or combina-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

tion packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

### IMDG

Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Remarks : IMDG Code segregation group - none  
IMDG: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provisions of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class all provisions of this Code relevant to any additional hazards continue to apply.

### IATA (Cargo)

Packing instruction (cargo aircraft) : 964  
Packing group : III  
Labels : Miscellaneous  
Remarks : IATA: These substances when transported in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

### IATA (Passenger)

Packing instruction (passenger aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : Miscellaneous

## 14.5 Environmental hazards

### ADR/RID/ADN

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

### IATA (Cargo)

Environmentally hazardous : yes

## 14.6 Special precautions for user

Remarks : The transport of dangerous goods, including their loading and unloading, must be done by people who received the neces-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

sary training required by Modal Regulations.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list: 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

: Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Council Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS

Seveso III Directive (2012/18/EU) implemented by Control of Major Accident Hazards Regulations 2015 (COMAH) E2 ENVIRONMENTAL HAZARDS

### 15.2 Chemical safety assessment

Not applicable



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

### SECTION 16: Other information

#### Full text of H-Statements

H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H360F	: May damage fertility.
H361f	: Suspected of damaging fertility.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10/50 Epoxy Casting Resin

Version  
10.0 SDB\_GB

Revision Date:  
25.06.2024

Date of last issue: 02.08.2022  
Date of first issue: 27.12.2012

Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Training advice : Provide adequate information, instruction and training for operators.

### Classification of the mixture:

Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
Repr. 1B	H360F
Aquatic Chronic 2	H411

### Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

GB / EN

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : GlassCast 10 Epoxy Hardener  
UFI : SYY0-P92Q-Y00S-TFM8

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Type of Application (Use) : Epoxy Hardener  
  
Recommended restrictions : Reserved for industrial and professional use.  
on use

#### 1.3 Details of the supplier of the safety data sheet

**Company name:** Easy Composites Ltd  
Unit 39, Park Hall Business Village  
Longton, Stoke on Trent  
Staffordshire  
ST3 5XA  
United Kingdom  
**Tel:** +44 (0) 1782 454499  
**Email:** sales@easycomposites.co.uk

**1.4 Emergency telephone number** +44 (0) 1782 454499  
(office hours only)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

Hazard pictograms



Signal word

: Danger

Hazard statements

: H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard  
Statements

: EUH071 Corrosive to the respiratory tract.

## Precautionary statements

### Prevention:

P261 Avoid breathing mist or vapours.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

**P303 + P361 + P353** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

**P304 + P340 + P310 IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

**Hazardous components which must be listed on the label:**

3-aminomethyl-3,5,5-trimethylcyclohexylamine

benzyl alcohol

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : Cycloaliphatic amine based mixture

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 612-067-00-9 01-2119514687-32	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412  specific concentration limit Skin Sens. 1A; H317 >= 0,001 %  Acute toxicity esti- mate  Acute oral toxicity: 1.030 mg/kg	>= 30 - < 50
benzyl alcohol	100-51-6 202-859-9 603-057-00-5 01-2119492630-38	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319	>= 20 - < 25
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with trimethylhexane-1,6-diamine	153195-44-9 500-332-0 01-2120781950-47-0001	Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Acute 1; H400 EUH071  M-Factor (Acute aquatic toxicity): 1	>= 12,5 - < 20
Poly[oxy(methyl-1,2-ethanediyl)], $\alpha$ -(2-aminomethylethyl)- $\omega$ -(2-aminomethylethoxy)-	9046-10-0 01-2119557899-12	Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 10 - < 12,5

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	25513-64-8 247-063-2 01-2119560598-25	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 1 - < 3
---	---	--	------------

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Show this safety data sheet to the doctor in attendance.  
Keep warm and in a quiet place.  
Take off all contaminated clothing immediately.
- If inhaled : Move to fresh air.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
Do NOT use solvents or thinners.  
If on clothes, remove clothes.  
Burns must be treated by a physician.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
If eye irritation persists, consult a specialist.  
If easy to do, remove contact lens, if worn.
- If swallowed : Do NOT induce vomiting.  
If a person vomits when lying on his back, place him in the recovery position.  
Call a physician immediately.  
Give small amounts of water to drink.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Burn  
superficial burning sensation  
Redness  
Severe irritation

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

Foam  
Dry powder  
Water mist

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : The pressure in sealed containers can increase under the influence of heat.  
Cool closed containers exposed to fire with water spray.  
Hazardous decomposition products formed under fire conditions.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Further information : In the event of fire and/or explosion do not breathe fumes.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Immediately evacuate personnel to safe areas.  
Prevent fire extinguishing water from contaminating surface water or the ground water system.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.  
Evacuate personnel to safe areas.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.  
Try to prevent the material from entering drains or water courses.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

Pick up and transfer to properly labelled containers.

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours or spray mist.  
Avoid inhalation, ingestion and contact with skin and eyes.  
Wear personal protective equipment.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : Provide adequate ventilation. Wash hands and face before breaks and immediately after handling the product.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.
- Further information on storage conditions : Protect from moisture.
- Advice on common storage : Keep away from isocyanates.  
Do not store near acids.  
Keep away from oxidizing agents.
- Further information on storage stability : Stable at normal ambient temperature and pressure.

### 7.3 Specific end use(s)

- Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.  
Contains no substances with occupational exposure limit values.

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

Substance name	End Use	Exposure routes	Potential health effects	Value
benzyl alcohol	Workers	Inhalation	Short-term exposure, Systemic effects	450 mg/m3
	Workers	Inhalation	Long-term exposure, Systemic effects	90 mg/m3
	Workers	Skin contact	Short-term exposure, Systemic effects	47 mg/kg
	Workers	Skin contact	Long-term exposure, Systemic effects	9,5 mg/kg
	Consumers	Ingestion	Short-term exposure, Systemic effects	25 mg/kg
	Consumers	Ingestion	Long-term exposure, Systemic effects	5 mg/kg
	Consumers	Inhalation	Short-term exposure, Systemic effects	40,55 mg/m3
	Consumers	Inhalation	Long-term exposure, Systemic effects	8,11 mg/m3
	Consumers	Skin contact	Short-term exposure, Systemic effects	28,5 mg/kg
	Consumers	Skin contact	Long-term exposure, Systemic effects	5,7 mg/kg
Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω-(2-aminomethylethoxy)-	Workers	Skin contact	Long-term systemic effects	2,5 mg/kg
	Workers	Skin contact	Long-term local effects	0,623 mg/cm2
	Consumers	Skin contact	Long-term systemic effects	1,25 mg/kg
	Consumers	Skin contact	Long-term local effects	0,311 mg/cm2
	Consumers	Ingestion	Long-term systemic effects	0,04 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
3-aminomethyl-3,5,5-trimethylcyclohexylamine	Fresh water	0,06 mg/l
	Marine water	0,006 mg/l
	Intermittent releases	0,23 mg/l
	Fresh water sediment	5,784 mg/kg
	Marine sediment	0,578 mg/kg
	Sewage treatment plant	3,18 mg/l
benzyl alcohol	Soil	1,121 mg/kg
	Fresh water	1 mg/l
	Marine water	0,1 mg/l
	Fresh water sediment	5,27 mg/kg
	Marine sediment	0,527 mg/kg
	Soil	0,456 mg/kg
	Sewage treatment plant	39 mg/l
	Intermittent releases	2,3 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω-(2-aminomethylethoxy)-	Fresh water	0,015 mg/l
	Marine water	0,0143 mg/l
	Fresh water sediment	0,132 mg/kg
	Marine sediment	0,125 mg/kg
	Soil	0,0176 mg/kg
	Intermittent releases	0,15 mg/l
	Sewage treatment plant	7,5 mg/l

### 8.2 Exposure controls

#### Engineering measures

Effective exhaust ventilation system  
effective ventilation in all processing areas

#### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166  
Do not wear contact lenses.  
Ensure that eyewash stations and safety showers are close to the workstation location.

#### Hand protection

Material : Protective gloves complying with EN 374.

Remarks : Nitrile rubber

#### Skin and body protection

: Protective suit  
Recommended preventive skin protection

#### Respiratory protection

: Use respirator when performing operations involving potential exposure to vapour of the product.  
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.  
Recommended Filter type:  
ABEK-filter  
Equipment should conform to EN 14387

#### Protective measures

: Avoid contact with skin.  
Wear suitable protective equipment.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : light yellow  
Odour : ammoniacal

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

Odour Threshold	:	not determined
Melting point/freezing point	:	Not applicable
Boiling point/boiling range	:	> 200 °C
Upper explosion limit / Upper flammability limit	:	Not applicable
Lower explosion limit / Lower flammability limit	:	Not applicable
Flash point	:	150 °C
Ignition temperature	:	Not applicable
Auto-ignition temperature	:	Not applicable
Decomposition temperature	:	No data available
pH	:	11 Concentration: 1 %
Viscosity		
Viscosity, dynamic	:	150 - 250 mPa.s (25 °C)
Viscosity, kinematic	:	not determined
Solubility(ies)		
Water solubility	:	not determined
Solubility in other solvents	:	not determined
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	not determined
Density	:	1 g/cm <sup>3</sup> (25 °C)
Bulk density	:	not determined
Relative vapour density	:	not determined
Particle characteristics		
Particle size	:	Not applicable

### 9.2 Other information

Explosives	:	Not applicable
------------	---	----------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

Oxidizing properties : Not applicable

Self-ignition : Not applicable

Evaporation rate : not determined

Surface tension : not determined

Sublimation point : Not applicable

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Stable under recommended storage conditions.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with the following substances:  
Acids  
Strong oxidizing agents

#### 10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

#### 10.5 Incompatible materials

Materials to avoid : Strong acids  
Strong oxidizing agents

#### 10.6 Hazardous decomposition products

This product may release the following:

Nitrogen oxides (NO<sub>x</sub>)  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

##### Product:

Acute oral toxicity : Acute toxicity estimate: 1.060 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Acute toxicity (other routes of administration) : Remarks: No data available

### Components:

#### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Acute oral toxicity : Acute toxicity estimate: 1.030 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

#### **benzyl alcohol:**

Acute inhalation toxicity : LC50 (Rat, male and female): 4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: yes

#### **Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω-(2-aminomethylethoxy)-:**

Acute oral toxicity : LD50 (Rat, male and female): 2.885,3 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): 2.979,7 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

### **Skin corrosion/irritation**

#### Product:

Remarks : No data available

### Components:

#### **benzyl alcohol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with trimethylhexane-1,6-diamine

:

Species : human skin  
Assessment : Causes burns.  
Method : OECD Test Guideline 431  
Result : Corrosive to skin  
GLP : yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

### **Poly[oxy(methyl-1,2-ethanediyl)], $\alpha$ -(2-aminomethylethyl)- $\omega$ -(2-aminomethylethoxy)-:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Corrosive

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks : No data available

#### **Components:**

##### **benzyl alcohol:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Eye irritation  
GLP : yes

### **Poly[oxy(methyl-1,2-ethanediyl)], $\alpha$ -(2-aminomethylethyl)- $\omega$ -(2-aminomethylethoxy)-:**

Method : OECD Test Guideline 405  
Result : Risk of serious damage to eyes.

### **Respiratory or skin sensitisation**

#### **Product:**

Remarks : No data available

### **Carcinogenicity**

#### **Product:**

Remarks : No data available

### **Reproductive toxicity**

#### **Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

### **STOT - single exposure**

#### **Product:**

Remarks : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

### STOT - repeated exposure

**Product:**

Remarks : No data available

### Repeated dose toxicity

**Product:**

Remarks : No data available

### Aspiration toxicity

**Components:**

**3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

No aspiration toxicity classification

## 11.2 Information on other hazards

### Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

**Product:**

Remarks : No data available

## SECTION 12: Ecological information

### 12.1 Toxicity

**Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

**Components:**

**3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 110 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: Directive 67/548/EEC, Annex V, C.1.  
GLP: yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 23 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : ErC50 (Scenedesmus capricornutum (fresh water algae)): > 50 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: Directive 67/548/EEC, Annex V, C.3.  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 3 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
GLP: yes

### benzyl alcohol:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 230 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 770 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with trimethylhexane-1,6-diamine

:  
Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 0,64 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 0,96 mg/l  
Exposure time: 72 h  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201  
GLP: yes

M-Factor (Acute aquatic toxicity) : 1



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

### **Poly[oxy(methyl-1,2-ethanediyl)], $\alpha$ -(2-aminomethylethyl)- $\omega$ -(2-aminomethylethoxy)-:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 15 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 80 mg/l  
aquatic invertebrates  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic : NOEC (Pseudokirchneriella subcapitata (green algae)): 0,32  
plants  
mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

## 12.2 Persistence and degradability

### **Product:**

Biodegradability : Remarks: No data available

Physico-chemical removabil- : Remarks: No data available  
ity

### **Components:**

#### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Biodegradability : Test Type: aerobic  
Result: Not readily biodegradable.  
Method: Directive 67/548/EEC Annex V, C.4.A.  
GLP: yes

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with trimethylhexane-1,6-diamine

:

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

### **Poly[oxy(methyl-1,2-ethanediyl)], $\alpha$ -(2-aminomethylethyl)- $\omega$ -(2-aminomethylethoxy)-:**

Biodegradability : Test Type: aerobic  
Result: Not readily biodegradable.  
Method: OECD Test Guideline 301B  
GLP: yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

### 12.3 Bioaccumulative potential

**Product:**

Bioaccumulation : Remarks: No data available

**Components:**

**3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Partition coefficient: n-octanol/water : log Pow: 0,99  
Method: OECD Test Guideline 107  
GLP: yes

**Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω-(2-aminomethylethoxy)-:**

Partition coefficient: n-octanol/water : log Pow: 1,34 (25 °C)  
Method: OECD Test Guideline 117  
GLP: yes

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : In accordance with local and national regulations.  
Container hazardous when empty.  
Do not dispose of with domestic refuse.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

Do not mix waste streams during collection.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR/RID/ADN : UN 2735  
IMDG : UN 2735  
IATA : UN 2735

#### 14.2 UN proper shipping name

ADR/RID/ADN : AMINES, LIQUID, CORROSIVE, N.O.S.  
(Isophorone diamine)  
IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.  
(ISOPHORONEDIAMINE)  
IATA : Amines, liquid, corrosive, n.o.s.  
(Isophorone diamine)

#### 14.3 Transport hazard class(es)

ADR/RID/ADN : 8  
IMDG : 8  
IATA : 8

#### 14.4 Packing group

ADR/RID/ADN  
Packing group : III  
Classification Code : C7  
Hazard Identification Number : 80  
Labels : 8  
Tunnel restriction code : E  
IMDG  
Packing group : III  
Labels : 8  
EmS Code : F-A, S-B  
Remarks : IMDG Code segregation group 18 - Alkalis

#### IATA (Cargo)

Packing instruction (cargo aircraft) : 856  
Packing group : III  
Labels : Corrosive

#### IATA (Passenger)

Packing instruction (passenger aircraft) : 852  
Packing instruction (LQ) : Y841

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

Packing group : III  
Labels : Corrosive

### 14.5 Environmental hazards

#### ADR/RID/ADN

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

Remarks : The transport of dangerous goods, including their loading and unloading, must be done by people who received the necessary training required by Modal Regulations.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list: 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

: Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

International Chemical Weapons Convention (CWC)  
Schedules of Toxic Chemicals and Precursors : Not applicable

Council Regulation (EC) No 111/2005 laying down rules  
for the monitoring of trade between the Community and  
third countries in drug precursors : Not applicable

Seveso III: Directive 2012/18/EU of the Euro-  
pean Parliament and of the Council on the  
control of major-accident hazards involving  
dangerous substances. Not applicable

Seveso III Directive (2012/18/EU) implemented  
by Control of Major Accident Hazards Regula-  
tions 2015 (COMAH) Not applicable

### 15.2 Chemical safety assessment

Not applicable

## SECTION 16: Other information

### Full text of H-Statements

H302 : Harmful if swallowed.  
H312 : Harmful in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H400 : Very toxic to aquatic life.  
H412 : Harmful to aquatic life with long lasting effects.  
EUH071 : Corrosive to the respiratory tract.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Skin Corr. : Skin corrosion  
Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## GlassCast 10 Epoxy Hardener

Version  
8.0 SDB\_GB

Revision Date:  
19.08.2022

Date of last issue: 03.12.2020  
Date of first issue: 27.12.2012

Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Training advice : Provide adequate information, instruction and training for operators.

#### Classification of the mixture:

Acute Tox. 4	H302
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 3	H412

#### Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

GB / EN