

Document group: 28-4877-8
Revision date: 22/09/2017
Transportation version number: 1.00 (08/11/2011)

Version number: 6.01
Supersedes date: 19/05/2016

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

No 8 Mould Release Wax

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Company name: Easy Composites Ltd
Unit 39, Park Hall Business Village
Longton, Stoke on Trent
Staffordshire
ST3 5XA
United Kingdom

Tel: +44 (0) 1782 454499

Fax: +44 (0) 1782 596868

Email: sales@easycomposites.co.uk

1.4. Emergency telephone number +44 (0) 1782 454499
(office hours only)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Flammable Solid, Category 1 - Flam. Sol. 1; H228
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SAFETY DATA SHEET

No 8 Mould Release Wax

SIGNAL WORD

DANGER.

Symbols:

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Naphthol Spirits (C11-C13)	64742-48-9	265-150-3	10 - 30
Pin-2(3)-ene	80-56-8	201-291-9	5 - 10
Pin-2(10)-ene	127-91-3	204-872-5	5 - 10

HAZARD STATEMENTS:

H228	Flammable solid.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

General:

P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.

Prevention:

P210A	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261A	Avoid breathing vapours.
P280E	Wear protective gloves.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

18% of the mixture consists of components of unknown acute oral toxicity.

Contains 65% of components with unknown hazards to the aquatic environment.

Notes on labelling

H304 is not required on the label due to the product's viscosity

Nota P applied for CASRN 64742-48-9. Nota N applied to CAS 64742-14-9

2.3. Other hazards

None known.

SAFETY DATA SHEET

No 8 Mould Release Wax

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Distillates (petroleum), acid-treated light	64742-14-9	265-114-7		10 - 30	Nota N Asp. Tox. 1, H304; STOT SE 3, H336; EUH066
Naphthol Spirits (C11-C13)	64742-48-9	265-150-3		10 - 30	Asp. Tox. 1, H304 - Nota P Aquatic Chronic 2, H411 STOT SE 3, H336; EUH066
Turpentine Gum	9005-90-7	232-688-5		10 - 20	Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1
Oxidised Polyethylene	68441-17-8			7 - 13	Substance not classified as hazardous
Carnauba Wax	8015-86-9	232-399-4		7 - 13	Substance not classified as hazardous
Conditioners	Trade Secret			5 - 10	Substance not classified as hazardous
Pin-2(10)-ene	127-91-3	204-872-5	01-2119519230-54	5 - 10	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1
Paraffin Wax	8002-74-2	232-315-6		5 - 10	Substance with a Community level exposure limit in the workplace
Pin-2(3)-ene	80-56-8	201-291-9		5 - 10	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get

SAFETY DATA SHEET

No 8 Mould Release Wax

medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the

SAFETY DATA SHEET

No 8 Mould Release Wax

workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Naphthol Spirits (C11-C13)	64742-48-9	Manufacturer determined	TWA:100 ppm	
Paraffin Wax	8002-74-2	UK HSC	TWA(as fume):2 mg/m ³ ;STEL(as fume):6 mg/m ³	

UK HSC : UK Health and Safety Commission
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

SAFETY DATA SHEET

No 8 Mould Release Wax

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Nitrile rubber.	No data available	No data available

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Appearance/Odour	Pleasant odour; Gold paste
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Boiling point/boiling range	<i>Not applicable.</i>
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Flammable Solid: Category 1. Flammable Solid: Category 1.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	65.6 °C [<i>Test Method</i> :Pensky-Martens Closed Cup] [<i>Details</i> :D93-90]
Autoignition temperature	<i>No data available.</i>
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Relative density	0.86 [<i>Ref Std</i> :WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	>=100 mPa-s
Density	0.86 g/cm ³

9.2. Other information

EU Volatile Organic Compounds	<i>No data available.</i>
Molecular weight	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

SAFETY DATA SHEET

No 8 Mould Release Wax

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

SAFETY DATA SHEET

No 8 Mould Release Wax

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE ₂₀ - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Naphthol Spirits (C11-C13)	Inhalation-Vapour (4 hours)		LC50 estimated to be 20 - 50 mg/l
Naphthol Spirits (C11-C13)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Naphthol Spirits (C11-C13)	Ingestion	Rat	LD50 > 5,000 mg/kg
Distillates (petroleum), acid-treated light	Dermal	Rabbit	LD50 > 2,000 mg/kg
Distillates (petroleum), acid-treated light	Ingestion	Rat	LD50 > 5,000 mg/kg
Carnauba Wax	Dermal		LD50 estimated to be > 5,000 mg/kg
Carnauba Wax	Ingestion	Rat	LD50 > 8,800 mg/kg
Oxidised Polyethylene	Ingestion	Rat	LD50 > 2,500 mg/kg
Paraffin Wax	Dermal	Rat	LD50 > 5,000 mg/kg
Paraffin Wax	Ingestion	Rat	LD50 > 5,000 mg/kg
Conditioners	Dermal	Rabbit	LD50 > 19,400 mg/kg
Conditioners	Ingestion	Rat	LD50 > 17,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Naphthol Spirits (C11-C13)	Rabbit	Mild irritant
Distillates (petroleum), acid-treated light	Professional judgement	Mild irritant
Carnauba Wax	Professional judgement	No significant irritation
Pin-2(3)-ene	In vitro data	Irritant
Oxidised Polyethylene	Professional judgement	No significant irritation
Pin-2(10)-ene	In vitro data	Irritant
Paraffin Wax	Rabbit	No significant irritation
Conditioners	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Naphthol Spirits (C11-C13)	Rabbit	Mild irritant
Distillates (petroleum), acid-treated light	Professional judgement	Mild irritant
Carnauba Wax	Professional	No significant irritation

SAFETY DATA SHEET

No 8 Mould Release Wax

	judgement	
Oxidised Polyethylene	Professional judgement	No significant irritation
Paraffin Wax	Rabbit	No significant irritation
Conditioners	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Naphthol Spirits (C11-C13)	Guinea pig	Not classified
Distillates (petroleum), acid-treated light	Guinea pig	Not classified
Pin-2(3)-ene	similar compounds	Sensitising
Pin-2(10)-ene	Mouse	Sensitising
Paraffin Wax	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Naphthol Spirits (C11-C13)	In Vitro	Not mutagenic
Naphthol Spirits (C11-C13)	In vivo	Not mutagenic
Distillates (petroleum), acid-treated light	In Vitro	Not mutagenic
Paraffin Wax	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Naphthol Spirits (C11-C13)	Not specified.	Not available	Not carcinogenic
Distillates (petroleum), acid-treated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Paraffin Wax	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Naphthol Spirits (C11-C13)	Not specified.	Not classified for female reproduction	Rat	NOAEL NA	pre mating & during gestation
Naphthol Spirits (C11-C13)	Not specified.	Not classified for male reproduction	Rat	NOAEL NA	28 days
Naphthol Spirits (C11-C13)	Not specified.	Not classified for development	Rat	NOAEL NA	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Naphthol Spirits (C11-C13)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL NA	

SAFETY DATA SHEET

No 8 Mould Release Wax

Naphthol Spirits (C11-C13)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Distillates (petroleum), acid-treated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), acid-treated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Distillates (petroleum), acid-treated light	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Paraffin Wax	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 15 mg/kg/day	90 days
Paraffin Wax	Ingestion	hematopoietic system liver immune system skin endocrine system bone, teeth, nails, and/or hair muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days

Aspiration Hazard

Name	Value
Naphthol Spirits (C11-C13)	Aspiration hazard
Distillates (petroleum), acid-treated light	Aspiration hazard
Pin-2(3)-ene	Aspiration hazard
Pin-2(10)-ene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Distillates (petroleum), acid-treated light	64742-14-9		Insufficient to classify			
Distillates (petroleum), acid-treated light	64742-14-9		Data not available or insufficient for classification			
Naphthol Spirits (C11-C13)	64742-48-9		Data not available or insufficient for			

SAFETY DATA SHEET

No 8 Mould Release Wax

			classification			
Turpentine Gum	9005-90-7	Fathead minnow	Estimated	96 hours	LC50	0.28 mg/l
Carnauba Wax	8015-86-9		Data not available or insufficient for classification			
Oxidised Polyethylene	68441-17-8		Data not available or insufficient for classification			
Pin-2(3)-ene	80-56-8	Fathead minnow	Experimental	96 hours	LC50	0.28 mg/l
Pin-2(3)-ene	80-56-8	Water flea	Experimental	48 hours	LC50	1.44 mg/l
Pin-2(10)-ene	127-91-3	Water flea	Experimental	48 hours	LC50	1.25 mg/l
Pin-2(10)-ene	127-91-3	Fathead minnow	Experimental	96 hours	LC50	0.5 mg/l
Conditioners	Trade Secret		Data not available or insufficient for classification			
Paraffin Wax	8002-74-2	Rainbow trout	Estimated	96 hours	LC50	>1,000 mg/l
Paraffin Wax	8002-74-2	Green algae	Estimated	96 hours	EC50	>1,000 mg/l
Paraffin Wax	8002-74-2	Water flea	Estimated	48 hours	EC50	>10,000 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Distillates (petroleum), acid-treated light	64742-14-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphthol Spirits (C11-C13)	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Turpentine Gum	9005-90-7	Estimated Biodegradation	28 days	BOD	92 % weight	OECD 301C - MITI test (I)
Carnauba Wax	8015-86-9	Estimated Biodegradation	28 days	CO2 evolution	96 % weight	OECD 301B - Modified sturm or CO2
Oxidised Polyethylene	68441-17-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Pin-2(3)-ene	80-56-8	Experimental Photolysis		Photolytic half-life (in air)	7.17 hours (t 1/2)	Other methods
Pin-2(3)-ene	80-56-8	Experimental Biodegradation	28 days	BOD	92 % BOD/ThBOD	OECD 301C - MITI test (I)
Pin-2(10)-ene	127-91-3	Experimental Photolysis		Photolytic half-life (in air)	4.9 hours (t 1/2)	Other methods
Pin-2(10)-ene	127-91-3	Estimated Biodegradation	28 days	BOD	92 % BOD/ThBOD	OECD 301C - MITI test (I)
Conditioners	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Paraffin Wax	8002-74-2	Estimated Biodegradation	28 days	BOD	40 % weight	OECD 301F - Manometric respirometry

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Distillates (petroleum), acid-treated light	64742-14-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphthol Spirits (C11-C13)	64742-48-9	Data not available	N/A	N/A	N/A	N/A

SAFETY DATA SHEET

No 8 Mould Release Wax

		or insufficient for classification				
Turpentine Gum	9005-90-7	Estimated Bioconcentration		Bioaccumulation factor	1300	Estimated: Bioconcentration factor
Carnauba Wax	8015-86-9	Estimated Bioconcentration		Bioaccumulation factor	7.4	Estimated: Bioconcentration factor
Oxidised Polyethylene	68441-17-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Pin-2(3)-ene	80-56-8	Experimental Bioconcentration		Log Kow	4.83	Other methods
Pin-2(10)-ene	127-91-3	Experimental Bioconcentration		Log Kow	4.16	Other methods
Conditioners	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Paraffin Wax	8002-74-2	Estimated Bioconcentration		Log Kow	10.2	Estimated: Octanol-water partition coefficient

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transportation information

IMDG: UN1325; Flammable Solid, Organic, N.O.S. (Petroleum Distillates); 4.1; II; Marine Pollutant: Alpha-Pinene; EMS: FA, SG.

IATA: UN1325; Flammable Solid, Organic, N.O.S. (Petroleum Distillates); 4.1; II.

ADR: UN1325; Flammable Solid, Organic, N.O.S. (Petroleum Distillates); 4.1; II; (E); F1.

SECTION 15: Regulatory information

SAFETY DATA SHEET

No 8 Mould Release Wax

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact manufacturer for more information The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

CLP: Ingredient table information was modified.

Section 3: Composition/ Information of ingredients table information was added.

Section 3: Composition/ Information of ingredients table information was deleted.

Section 9: Flash point information information was added.

Section 9: Property description for optional properties information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Biocumulative potential information information was modified.

Section 13: Standard Phrase Category Waste GHS information was modified.

Section 14: Transportation classification information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.